

TPF-5(230)

Evaluation of Plant-Produced High-
Percentage RAP Mixtures in the Northeast

Technical Committee Project Closeout Meeting

April 19, 2016

Research Team

University of New Hampshire

Dr. Jo Sias Daniel, PE (Project PI)



University of Massachusetts Dartmouth

Dr. Walaa Mogawer, PE



Rutgers University

Dr. Tom Bennert, PE



NC State University

Dr. Y. Richard Kim, PE



Pooled Fund Participants

- New Hampshire (NH DOT) - Lead Agency
- Maryland (MDOT)
- New Jersey (NJ DOT)
- New York (NYSDOT)
- Pennsylvania (PennDOT)
- Rhode Island (RIDOT)
- Virginia (VDOT)
- Federal Highway Administration (FHWA)

Project Objectives

- Evaluate the performance of plant-produced RAP mixtures in terms of low temperature and fatigue cracking
- Impact of plant production variables on material properties (temps, silo storage time)
- Produce better performing mixtures while also using higher RAP contents

Project Phases


- Phase I (2010): 18 mixtures, 3 plants: NH, NY, VT, up to 40% RAP, different virgin PG grades
- Phase II (2011): 10 additional mixtures from NH and VA, 25% RAP silo storage study mixtures
- Phase III (2013): Controlled laboratory study with 20% & 40% RAP, two binder grades, range of binder contents
- Silo Storage Study Task (2014): virgin & 25% RAP mixture sampled at multiple storage times up to 10 hours

Testing


- Virgin & Recovered Binder
 - PG grade and DSR master curve
 - CCT
 - ABCD
 - 4 mm diameter DSR
- Mixture
 - Dynamic Modulus
 - Hamburg & TSR
 - Low Temperature
 - Creep & Strength
 - TSRST
 - Fatigue
 - AMPT S-VECD protocol
 - Overlay Tester
 - Beam Flexure
 - AMPT Triaxial Stress Sweep (rutting)

**PHASE I & PHASE II
RAP CONTENT AND PG GRADE**


Phase I: NH PMPC




Phase I: NY PG 64-22 PMPC





NY 30% RAP Comparison




NY 40% RAP Comparison



Impact of Reheating: $|E^*|$





Impact of Reheating: $|E^*|$ Ratio







Recovered Binders

- RAP stiffens material
 - 1-3°C increase in high PG with each 10% RAP
 - 1-2°C increase in low PG with each 10% RAP










Virginia Mixtures



Plant vs Lab, Reheat and Field

Virgin PG 58-28



Virgin PG 58-28**15% RAP 58-28****25% RAP 58-28****25% RAP 52-34****30% RAP 52-34****40% RAP 52-34**

Phase I & II Summary


- Amount of stiffening impacted by:
 - Specimen preparation
 - RAP stiffness (soft VT RAP)
 - Virgin binder grade
 - Production parameters (temp, silo)
- Cracking resistance decreased, results mixed depending on test
- Dropping PG grade: mixed results

PHASE III LABORATORY STUDY



Phase III Testing Plan

Mixture	Asphalt content	RAP Content (total weight)		
		0	20	40
NH Phase I	Opt-0.5%	PG 64-28	PG 64-28 PG58-28	PG 64-28 PG 58-28
	Opt	PG 64-28	PG 64-28	PG 64-28
	Opt+0.5%	-	-	PG 64-28

Recovered Binder Grades




Dynamic Modulus









(a)

Overlay Tester




LVECD Fatigue Analysis






Permanent Deformation – RAP content



Permanent Deformation – % ac



Phase III Summary

- Better cracking performance
 - Softer PG, higher asphalt content, lower RAP content
 - Impacts of RAP greater at low asphalt content
- Better rutting performance
 - Harder PG, lower asphalt content, higher RAP content

SILO STORAGE STUDY ADDITIONAL TASK


Silo Storage Study Task

- Early phases indicated likely impact of silo storage time on measured properties
- Targeted study to evaluate storage time
- Materials
 - Virgin mixture
 - PG 64-22,12.5 mm NMAS
 - 0, 2.5, 5, 7.5 hours
 - 25% RAP mixture
 - PG 64-28,12.5 mm NMAS
 - 0, 2.5, 5, 7.5, 10 hours
- End of season
 - high production temperature ←




Source: www.hellotrade.com




Binder: Glover-Rowe Parameter






Binder: Glover-Rowe Parameter



Dynamic Modulus Master Curves



LVECD Pavement Life Evaluation



Summary of Observations

- Dropping PG grade not effective in all cases
- Virgin binder grade, RAP stiffness, and binder source important
- Plant conditions have impact on measured properties
 - Temperature, storage time
- Specimen fabrication technique matters
 - Reheating, Lab vs field
- Current laboratory protocols don't always capture what happens in the plant
- Need to use engineering judgement



QUESTIONS & DISCUSSION