TRANSPORTATION POOLED FUND PROGRAM QUARTERLY PROGRESS REPORT

Date: <u>March 31, 2017</u>

Lead Agency (FHWA or State DOT): _____Indiana DOT_

INSTRUCTIONS:

Project Managers and/or research project investigators should complete a quarterly progress report for each calendar quarter during which the projects are active. Please provide a project schedule status of the research activities tied to each task that is defined in the proposal; a percentage completion of each task; a concise discussion (2 or 3 sentences) of the current status, including accomplishments and problems encountered, if any. List all tasks, even if no work was done during this period.

Transportation Pooled Fund Program Project #	Transportation Pooled Fund Program - Report Period:	
(i.e, SPR-2(XXX), SPR-3(XXX) or TPF-5(XXX)	XQuarter 1 (January 1 – March 31)	
<u>TPF 5-238</u>	□Quarter 2 (April 1 – June 30)	
	□Quarter 3 (July 1 – September 30)	
	Quarter 4 (October 1 – December 31)	

Project Title:

Design and Fabrication Standards to Eliminate Fracture Critical Concerns in Steel Members Traditionally Classified as Fracture Critical

Name of Project Manager(s):	Phone Number:	E-Mail
Tommy E. Nantung	(765) 463-1521 ext. 248	tnantung@indot.in.gov
Lead Agency Project ID:	Other Project ID (i.e., contract #):	Project Start Date: 8/1/2011
Original Project End Date:	Current Project End Date:	Number of Extensions:
7/31/2014	7/31/2014	None

Project schedule status:

X On revised schedule

□ Ahead of schedule

 \Box Behind schedule

Overall Project Statistics:

Total Project Budget	Total Cost to Date for Project	Percentage of Work Completed to Date
\$790,000	\$790,000	100%

Quarterly Project Statistics:

Total Project Expenses	Total Amount of Funds	Total Percentage of
and Percentage This Quarter	Expended This Quarter	Time Used to Date
\$0	0.0%	100%

Project Description:

The objective of this research project is to take advantage of the major advances that have occurred in the past 30 years in the following areas related to fracture control in steel bridges:

- 1. The very high toughness of high performance steel (HPS), which was not available 30 years ago, can be used to take brittle fracture off the table so to speak. Crack arrest and very large defect tolerance can be ensured in these steels. Similar strategies have been employed by other industries for several years.
- 2. Modern fatigue design and detailing can ensure fatigue cracking does not occur.
- 3. Modern fabrication, shop inspection and the AWS FCP, greatly reduces the likelihood that defects are not introduced during fabrication. Advancements in NDT techniques along with technologies not regularly used, such as phased array UT have the potential to further reduce the chance of a defect being missed.

Progress this quarter (includes meetings, work plan status, contract status, significant progress, etc.):
Draft Final report summarizing Phase II full-scale testing and FEA is was completed

Anticipated work next quarter:

• Submit Phase II final report for review in April 2017

Significant Results:

During the past quarter, the major steps forward included:

1. The final report for Phase II was nearly completed

Circumstance affecting project or budget. (Please describe any challenges encountered or anticipated that might affect the completion of the project within the time, scope and fiscal constraints set forth in the agreement, along with recommended solutions to those problems).

Potential Implementation: None to date