TRANSPORTATION POOLED FUND PROGRAM QUARTERLY PROGRESS REPORT

Date: <u>Sept 30, 2017</u>			
Lead Agency (FHWA or State DOT):Indiana DOT			
NSTRUCTIONS: Project Managers and/or research project investing the projects are active. Project task that is defined in the proposal; a perotect the current status, including accomplishments adduring this period.	lease provide a centage compl	a project schedule statu etion of each task; a cor	s of the research activities tied to ncise discussion (2 or 3 sentences) of
Transportation Pooled Fund Program Project # (i.e. SPR-2(XXX), SPR-3(XXX) or TPF-5(XXX)		Transportation Pooled Fund Program - Report Period:	
		□Quarter 1 (January 1 – March 31)	
<u>TPF 5-253</u>		□Quarter 2 (April 1 – June 30)	
		X Quarter 3 (July 1 – September 30)	
		□Quarter 4 (October 1 – December 31)	
Project Title: Evaluation of Member Level Redundancy in	n Built-up Ste	el Members	
Name of Project Manager(s): Tommy E. Nantung	Phone Number: (765) 463-1521 ext. 248		E-Mail tnantung@indot.in.gov
Lead Agency Project ID:	Other Project ID (i.e., contract #):		Project Start Date: 9/1/2011
Original Project End Date: 8/31/2014	Current Project End Date: 7/31/2016		Number of Extensions: One
Project schedule status:			
☐ On schedule X On revised schedu Overall Project Statistics:	lle	☐ Ahead of schedu	ule
•		t to Date for Project	Percentage of Work
#70F 000*	MC77.050		Completed to Date
\$725,000*	\$677,258		96%
Quarterly Project Statistics:			
Total Project Expenses and Percentage This Quarter	Total Amount of Funds Expended This Quarter		Total Percentage of Time Used to Date
\$24,238	3.3 %		100%

Reflects budget increase due to partner states fulfilling commitments

Project description:

The objective of this research project is to quantify the redundancy possessed by built-up members. For example, a riveted built-up member will not typically "fail" if one of the components fractures. However, there is very little experimental data which is available to quantify the remaining fatigue life or strength of a member in which one of the components has failed. Furthermore, if built-up members are located in bridges classified as fracture critical, when significant member redundancy can be shown the bridge may not need to be classified as FC. However, doing so would release these members from the more rigorous arms-length inspection currently required. As a result, should a component fail, it may go undetected for an extended interval. Thus, a portion of the project is devoted to setting rational inspection intervals for these members. Lastly, the advantages of using built-up members fabricated with HPS components fastened using HS bolts in new construction will also be explored.

Progress this quarter (includes meetings, work plan status, contract status, significant progress, etc.):

- AASHTO T14 has voted to move the Proposed Guide Specifications forward for the 2018 SCOBS meeting in Burlington VT.
- Continued with FEA parametric studies for axially loaded members
- Prepared ballot-ready Guide Specification for consideration for 2018 SCOBS meeting
- Continued on development of step-by-step examples to provide guidance on how to use the proposed Guide Specifications.

Anticipated work next quarter:

- Continue working on parametric studies associated with axial members.
- Test additional prototype axial test specimen.
- Prepare a new ballot for evaluating flexural members for consideration by AASHTO T-14 for the August midyear meeting in Denver.

Significant results:

During the past guarter, the major steps forward included:

- 1. Gained additional support from AASHTO T-14 and FHWA to prepare ballot item related to specifications for evaluating internal redundancy in built up members.
- 2. Design and testing of the second axially loaded specimen.

Circumstance affecting project or budget. (Please describe any challenges encountered or anticipated that might affect the completion of the project within the time, scope and fiscal constraints set forth in the agreement, with recommended solutions to those problems).

Potential Implementation:

Working with T-18, T-14, and FHWA to develop specification language for implementation of results into MBE for riveted members subjected to flexure. Draft AASHTO-ready specification language has been prepared and the RT will continue to work with AASHTO to move the research into practice.